

# MINI Family

MINI Family



LN75-R25Q



LN75-R25QS


LN75-R25QT



With Trim

Trimless


White



Black



LN75-R25QS



20mm  
0.78"  
29mm  
1.14"  
∅ 25mm  
0.98"

53mm  
2.08"

LN75-R25QT



25mm  
0.98"  
60mm  
2.36"  
∅ 29mm  
1.14"

58mm  
2.28"

### Basic Information

Model	LN75-R25QS/T
Embedded Parts	White
Mounting	Recessed
Trim Finishing Color	White
Reflector Color	White/Black
Material	Cold Forged Pure Alu. (Heat Sink)/Die-casting Alu.
Cutout Size	∅ 25mm / ∅ 29mm
IP Rating	IP20
Power	Max.6W
Input Voltage	DC36V
Input Current	Max. 120mA

### Optical Parameters

Light Source	LED COB
Lumens	45lm/W
CRI	90Ra
CCT	3000K ● 3500K ● 4000K ○
Beam Angle	▲ 15° ▲ 25° ▲ 20° x 50°
UGR	< 10
LED Lifespan	50000hrs

Driver Voltage AC100-120V AC220-240V

Driver Options ON/OFF

LN75-R26Q



LN75-R26QS

LN75-R26QT



With Trim

Trimless


White




Black




Gold



LN75-R26QS



LN75-R26QT



### Basic Information

Model	LN75-R26QS/T
Embedded Parts	With Trim/Trimless
Mounting	Recessed
Trim Finishing Color	White
Reflector Color	White/Black/Gold
Material	Pure aluminum
Cutout Size	∅ 25mm / ∅ 29mm
Light Direction	↓ 90° ↻ 360°
IP Rating	IP20
Power	Max. 8W
Input Voltage	DC36V
Input Current	Max. 200mA

### Optical Parameters

Light Source	LED COB
Lumens	65lm/W 90lm/W
CRI	97Ra/90Ra
CCT	3000K ● 3500K ● 4000K ○
CCT Changeable	2700K — 6000K 1800K — 3000K
Beam Angle	▲ 15° ▲ 25° ▲ 35°
UGR	< 9
LED Lifespan	50000hrs

Driver Voltage	AC100-120V AC220-240V
Driver Options	ON/OFF DIM TRIAC/ PHASE-CUT DIM 0/1-10V DIM DALI