









49mm 1.85"











#### HG-S05QS

#### HG-S05QT









## Basic Information

Model	HG-S05QS/S05QT
Embedded Parts	With Trim/Trimless
Mounting	Recessed
Trim Finishing Color	White/Black
Reflector Color	White/Black
Material	Aluminum
Cutout Size	[∄]163*44mm
IP Rating	IP20
Power	Max. 12W
Input Voltago	DC15V
Input Current	Max. 750mA

# Optical Parameters

Light Source	LED
Lumens	67lm/W
CRI	95Ra
ССТ	3000K • 3500K • 4000K •
CCT Changeable	2700K 6000K
Beam Angle	<b>№</b> 50°
LED Lifespan	50000hrs

Driver Voltage	AC100-120V AC220-240V			
Driver Options	ON/OFF	DIM TRIAC/ PHASE-CUT	DIM 0/1-10V	DIM DALI


















#### HG-S10QT

#### HG-S10QS





## Basic Information

Model	HG-S10QS/S10QT
Embedded Parts	With Trim/Trimless
Mounting	Recessed
Trim Finishing Color	White/Black
Reflector Color	White/Black
Material	Aluminum
Cutout Size	[∄]319*44mm
IP Rating	IP20
Power	Max. 24W
Input Voltage	DC30V
Input Current	Max. 750mA

## Optical Parameters

Light Source	LED
Lumens	67lm/W
CRI	95Ra
ССТ	3000K • 3500K • 4000K •
CCT Changeable	2700K 6000K
Beam Angle	<b>5</b> 0°
LED Lifespan	50000hrs

Driver Voltage	AC100-12	0V AC220-240V		
<b>Driver Options</b>	ON/OFF	DIM TRIAC/ PHASE-CUT	DIM 0/1-10V	DIM DALI

# HIGH Grille Series













## Basic Information

Model	HG-S05M
Mounting	Surface mounted
Trim Finishing Color	White/Black
Poflostor Color	White/Black
Material	Aluminum
IP Rating	IP20
Power	Max. 12W
Input Voltage	DC15V
Input Current	Max. 750mA

## Optical Parameters

Light Source	LED
Lumens	67lm/W
CRI	95Ra
ССТ	3000K ● 3500K ● 4000K ○
CCT Changeable	2700K 6000K
Beam Angle	<b>∑</b> 50°
LED Lifespan	50000hrs

Driver Voltage	AC100-120V AC220-240V			
Driver Options	ON/OFF	DIM TRIAC/ PHASE-CUT	DIM 0/1-10V	DIM DALI